

MISSION-BASED.
PERFORMANCE-DRIVEN.



TDFM-136B

ANALOG/DIGITAL
VHF/FM TRANSCEIVERS

TDFM-136B

ANALOG/DIGITAL VHF/FM TRANSCEIVERS

The all new Technisonic TDFM-136B is a Project 25 U.S. Forest Service compliant airborne VHF/FM transceiver. Providing digital or conventional analog FM communications on every currently available channel from 136 to 174 MHz within the VHF/FM band. The new 136B has been designed from the ground up with your forestry mission in mind as a drop-in replacement for existing Technisonic and NPX radio sets.

- The TDFM-136B operates on the Common Air Interface and is capable of multimode operation at 12.5 kHz analog* and Project 25 12.5 kHz digital modulation on a channel-by-channel basis.
- The TDFM-136 transceiver features a Two Channel Synthesized Guard receiver.
- Allows up to 230 non-volatile memory positions (channels) via front panel 12 button key pad, or downloaded from a PC.
- Direct Entry or Simplex mode is accomplished by simply keying in the desired operating frequency.
- A 48-Character, 2 line LED matrix display, is available in green or optional NVG compatible.
- Support of unique CTCSS and DCS signaling for transmit and receive frequencies.
- New architecture is based on Digital Signal Processor (DSP) technology and does not depend on availability of proprietary chip sets from competitive vendors.
- A USB upload/download function allows the operator to program all radios via a PC.
- Scan enabled across any or all of the channels stored in the preset memory positions.
- The TDFM-136B transceiver is panel-mounted (standard Dzus) and completely self-contained in a 3.0" (H), 5.75" (W) and 8.0" (D) chassis weighing just 3.5 pounds.
- Front panel controls are MAIN for main channel volume, GUARD for guard channel.



TDFM-136B GENERAL SPECIFICATIONS

Frequency Range:

136.000 MHz to 174.000 MHz

Operating Modes:

Project 25 CAI and conventional analog simplex or semi duplex

P25 Conventional Digital Mode

Channel Spacing: 12.5 /25 kHz * (230 Preset Channels)

Dimensions: 3.0" (H), 5.75" (W) and 8.0" (D)

Weight: 3.5 Lbs (1.6 Kg)

Temperature Range: -45°C to 70°C

Power Requirement: 28 V DC

Certification: FCC and DOC Type Approved

Guard receiver: 2 channel synthesized

CTCSS Squelch Capability:

Encodes/decodes all 64 available tones

DPL/DCS capability: All available digital squelch codes

DTMF Encoder: All standard DTMF tones supported

Audio Output: 500mW into 600 ohms

Speaker Output: 2.5 Watts into 4 ohms

Backlighting: 28V DC or 5V DC, software selectable

* 25 kHz analog operation is only enabled where permitted by statute

MORE CAPABLE. LESS COST.

New Customer Inquiries

Jim Huddock
Minneapolis, MN
612.231.9020

Corporate Headquarters

240 Traders BLVD.
Mississauga, ON Canada L4Z 1W7
905.890.2113